

# Power-PRO™ XT

## Powered Ambulance Cot



3800 E. Centre Avenue  
Portage, MI 49002 USA  
t: 269 329 2100  
toll free: 800 327 0770  
ems.stryker.com

### Standard Features

- Automatic in-cot fastener shut-off
- Manual back-up release handle
- Automatic high-speed retract
- Battery-powered hydraulic lift system
- Preventative maintenance hour meter
- Battery pack power level indicator
- Settable load height with jog function
- Color-coded controls
- High visibility powder-coated frame
- Lightweight, rugged aluminum construction
- Optimized lift bar and control design
- Lower lifting bar
- Lift-capable safety bar
- Integrated bumper system
- Retractable head section
- Floor-mounted safety hook
- One-hand release, fold down siderails
- One-hand release, infinite positioning, pneumatically assisted backrest
- Oversized wheels with sealed caster and wheel bearings
- Sealed bolster mattress
- Shock or flat leg positioning
- Two lap belts and one four-point shoulder restraint
- Built-in pull handle
- X-frame guards
- Power washable
- SMRT power system (12V DC, 120V AC and 240V AC options available)

### Optional Features

- Heavy duty two- or three-stage IV poles (patient right or left)
- Permanent or removable O<sub>2</sub> bottle holders (head end, foot end or fowler)
- Sealed flat mattress
- Dual wheel locks
- Head extension
- Pillow
- Equipment hook
- Backrest storage pouch
- Head end storage flat
- Defibrillator platform
- Base storage net
- Knee gatch
- SMRT charger mounting bracket
- Power-LOAD™ compatibility

### Specifications

<b>Model Number</b>	<b>6506</b>
<b>Height<sup>1</sup></b> (infinite height positioning between lowest and highest position)	
Highest Position	41.5 in. (105 cm)
Lowest Position	14 in. (36 cm)
<b>Length</b>	
Standard	81 in. (206 cm)
Minimum	63 in. (160 cm)
<b>Width</b>	23 in. (58 cm)
<b>Weight<sup>2</sup></b>	125 lb (57 kg)
<b>Wheels</b>	
Diameter	6 in. (15 cm)
Width	2 in. (5 cm)
<b>Articulation</b>	
Backrest	0–73°
Shock Position	+15°
Optional Knee Gatch	30°
<b>Maximum Weight Capacity<sup>3</sup></b>	700 lb (318 kg)
<b>Minimum Operator Required</b>	
Occupied Cot	2
Unoccupied Cot	1
<b>Recommended Fastener System</b>	
Power-LOAD	Model 6390
Floor Mount	Model 6370 or 6377
Wall Mount	Model 6371
<b>Recommended Loading Height<sup>4</sup></b>	Up to 36 in (91 cm)

### Warranty

- Two-year parts, and labor
- Two year bumper to bumper
- One-year soft goods
- Three-year X-frame components
- Three-year limited powertrain
- Lifetime on all welds

### Extended warranties available.

7-year service life.

<sup>1</sup> Height measured from bottom of mattress, at seat section, to ground level.

<sup>2</sup> Cot is weighed with one battery pack, without mattress and restraints.

<sup>3</sup> 700 lb weight capacity with an unassisted lift capacity of 500 lb (Cot loads over 300 lb (136 kg) may require additional assistance to meet the set cot load height).

<sup>4</sup> Can accommodate load decks up to 36 in. Load height can be set between 26 in and 36 in.

Stryker reserves the right to change specifications without notice.

In-service video included with every order.

The Power-PRO XT is designed to conform to the Federal Specification for the Star-of-Life Ambulance KKK-A-1822.

The Power-PRO XT is designed to be compatible with competitive cot fastener systems.

The yellow and black color scheme is a registered trademark of Stryker Corporation

Meets dynamic crash standards with Power-LOAD cot fastening system (AS/NZS-4535, BS EN-1789 with X-restraints and SAE J3027) and Performance-LOAD cot fastening system (SAE J3027 with X-restraints).

Stryker Corporation or its divisions or other corporate affiliated entities own, use or have applied for the following trademarks or service marks: **Power-LOAD, Power-PRO, Stryker**, . All other trademarks are trademarks of their respective owners or holder.

